



Color: **White**  
Panel: **STANDARD**

- LED backlit control panel
- Temperature display resolution 0,1°C
- Audible and visual alarms
- Dry contact for alarms signal remoting

## TECHNICAL FEATURES

Product Code	AQL600A
Temperature	-5°C / -20°C
Refrigeration Type	Forced air
Defrost Type	Automatic, with heating resistance
Condensate Evaporation	Automatic
Refrigerant Gas	R290
Climatic Class	+16°C / +32°C (N)
Gross Capacity (liters)	1295
Net Capacity (liters)	1160
External Dimensions (W x D x H mm)	1500 x 770 x 2080

## TECHNICAL FEATURES

Packaging Dimensions (W x D x H mm)	1560 x 940 x 2240
-------------------------------------	-------------------

## ELECTRICAL DATA

Power Supply (V/ph/Hz)	220-230/1/50
Power Plug	Type F

## STRUCTURAL FEATURES

Structure	Upright
External Material	Anti-bacterial coated steel white colour
Insulation Thickness (mm)	75
Triple-Layer Heated Glass Door	Yes
Automatic Door Closure	Yes
Internal Lighting Type	LED stripe with UVA for air sterilization
Shelves Number	6
Shelf Material	Wire steel with white colour plastic coating
Shelves Dimensions (W x D mm)	530 x 550
Shelf Adjustment Step Range (mm)	89
Drawers with extractable slides	Optional
Drawer Adjustment Step Range (mm)	89

## CONTROL PANEL

Display Type	LED
Access Password	No
Probe Type	Nr. 2 NTC
Alarm Signaling	Acoustic and visual
Alarm Indications	Codes

## CONTROL PANEL

Adjustable High/Low Temperature Alarm	Yes
Adjustable Door Open Alarm	Yes
Power Loss Alarm	Yes
Probe Fault Alarm	Yes
Acoustic Alarm Silencing Options	Yes
Calibration	Yes
Alarm Memory	10
Dry Contact	Yes (NC)

## ACCESSORIES

Open wire shelf
Stainless steel open wire shelf
Chromium plated open wire basket
Stainless steel drawer
Plastic drawer divider
Drawer Perspex front shield
Castors Ø 95 mm, 2 with brakes
Door key locking
Temperature chart recorder
Data-logger function with USB port (available for xPRO control panel only)
Ballasted sensor for simulation of the product temperature alarm (available for xPRO control panel only)
Internal electrical socket
Porthole with cover Ø 18 mm
Refrigerant R452a
GSM/GPRS telephone dialer
Voltage 230V/1ph/60Hz
Voltage 115V/1ph/60Hz

## ACCESSORIES

Plug type A

Plug type B

Plug type G

Plug type I

Wooden crate packing

IQ Documentation

OQ Documentation

PQ Documentation